

User Manual

Human machine interface PROFINET IO Slave

GRAPHIC SYMBOLS



INFORMATION, It helps users with more details about the topic and failure to follow may lead to unpredictable results.



WARNING, Failure to follow may lead to minor injury or damage / malfunctioning of equipment



DANGER, Failure to follow may lead to injury or fatal accident to operating personal or damage/malfunctioning of equipment



CAUTION, Failure to follow may lead to malfunctioning of equipment, damage or repair



Protective Earth



DC Supply

PREFACE

Original equipment manufacturer reserves the right to change information available in this document without notice. Original Equipment manufacturer is not liable for any damages incurred to equipment/personal during installation or use of equipment as explained in this document. User must acquire sufficient knowledge & skills prior to use the equipment in the application and follow all the local standards & regulations to meet safety requirements

PROFINET IO[®], is registered trade mark of PNO
Simatic manager[®], is registered trade mark of SIEMENS
Anybus-CC[®], is registered trade mark of HMS

TABLE OF CONTENTS

1. OVERVIEW	4
1.1 INTRODUCTION	4
1.2 COMMUNICATION	5
2. SPECIFICATIONS	5
3. EXTENSION CARD INSTALLTION	6
4. WIRING	8
5. QUICK SETUP	9
6. PLC CONFIGURATION	11
7. HMI CONFIGURATION	21
8. CONVERTER	24
9. EXAMPLES	26
9.1.1 4 words Read, 2 words write	26
9.1.2 8 bits Read, 8 bits write	28
10. FAQ	33

1. OVERVIEW

1.1 Introduction

PROFINET is the open industrial Ethernet standard of PROFIBUS & PROFINET International (PI) for automation. PROFINET uses TCP/IP and IT standards, and is, in effect, real-time Ethernet. The PROFINET concept features a modular structure.

ProfiNet IO Master




Fig: Typical configuration

HMI supports Profinet IO communication via optional extension card.
Check HMI ordering code for Network extension card availability

Profinet IO slave interface file will be supplied

1.2 Communication




Fig: Data exchange between master and slave

2. SPECIFICATIONS

Item	Description
COM port number in HMI	COM3 (for network option, extension card)
ProfiNet IO extension card name (Device Name)	ABCC-PRT
Master to Slave, maximum bytes	256
Slave to Master, maximum bytes	256
Total bytes	512
Supported data types	byte, Int16 & Int32
Device number	128 maximum, set from Master
XML file name	GSDML-V2.2-HMS-ABCC-PRT-20100329
Maximum distance between Master and Slave on Ethernet 100BASE-TX	100 meters
Number of Ethernet Ports	1

3. EXTENSION CARD INSTALLTION

COM3 is dedicated for extension card. It is clearly marked on rear side of HMI.

Check HMI ordering code for Network extension card availability




Fig: Typical dimensional drawing of HMI 7"




Fig: Typical HMI 7" with ProfiNet IO module



1. Open HMI rear cover by removing all the screws
2. Remove M2 X 4 mm screws (2 nos.) and open network module blank cover
3. Remove 5 mm hex screws (2 nos.) for COM1 port using tool 5mm Hex nut screwdriver
4. Remove COM1 cover. At this time, COM1 enclosure will be opened. Note down the direction of enclosure carefully as it need to fit in same direction later
5. Remove 5 mm hex screws for network extension card
6. Now, insert network extension card into main board and make sure it is properly inserted with in guider pins




Fig: Extension card connector and guider


7. Fix COM1 cover properly and make sure that PCB is locked with in locking holes
8. Fix 5 mm hex screws (2 nos.) for COM1 port
9. Fix network module cover. Remember, these covers are different for different network extension modules. You will receive specific network module cover along with network extension card
10. Fix 5 mm hex screws (2 nos.) for network extension card. If required gently push network extension card downside to allow screws go inside properly
11. Fix M2 X 4 mm screws (2 nos.) on network module cover. If required gently push network extension card downside to allow screws go inside properly
12. Close the HMI rear cover

4. WIRING

Standard Ethernet cable can be used for ProfiNet IO communication. Please refer ProfiNet IO website for more details about physical media and topologies

<http://www.profibus.com/technology/profinet/>

5. QUICK SETUP



Tips



Steps


1. First decide how much data to be exchanged between Master and Slave.
2. In HMI configuration, create required Read blocks (Master to Slave) first, then, write blocks (Slave to Master).
3. Open Tag data base from Project explorer. It is possible to modify blocks to Tag names at Tag database here. Once block name is changed to Tag name, never attempt to delete the ProfiNet IO setup from connection as you will lose all the Tag names.
4. Link tags with Objects like Label, Text box etc... Once Tag is linked with objects, never attempt to delete ProfiNet IO configuration from Connections.
5. Make sure HMI is connected to PC on Ethernet network. Download application from PC to HMI



6. Switch OFF power supply to HMI. Press your finger on HMI active screen area and then switch ON the power. On Control center, press "Run".
7. Now, in Simatic Manager software, scan for Profinet devices. Slave should be detected by Simatic manager.

6. PLC CONFIGURATION

How to configure ProfiNet IO slave in Simatic Manager


1. Obtain GSDML-V2.2-HMS-ABCC-PRT-20100329 file from factory. Store the file in desktop
2. Open Simatic Manager software, preferably the latest version V5.4 or above
3. Install XML file into Simatic Manager







ABCC-PRT should be visible at above location


4. Add ProfiNet IO system






5. Select "RT" icon as shown below, drag and drop on ProfiNet IO system line






Double click at ABCC-PRT slave



Note: Please do not change Device name here. Other wise, communication will not work

Enter Slave device number here.

Click "Ethernet" and enter unique IP address for the ProfiNet slave device. Please note down this IP address, you must enter the same address at HMI during ProfiNet slave configuration






6. Add IO modules for data exchange.

Various types of IO modules available are as follows.

Slave to Master (Input)	Master to Slave (Output)	Input/Output
1 byte in	1 byte out	Null
1 word in	1 word out	Null
2 words in	2 words out	Null
4 words in	4 words out	Null

Select APCC-PRT slave, then, click "Slot1", right click mouse to Insert objects



SIMATIC 300 Station (Configuration) -- AN_PNIO

(0) UR

1	PS 307 2A
2	CPU 315-2 PN/DP
X1	MPV/DP
X2	PN-IO
X2 P1	Port 1
3	
4	AI4/AO2
5	DI8/DO8xDC24V/0,5A
6	
7	
8	
9	
10	


Ethernet(1): PROFINET-IO-System (100)

(1) ABCC-P
DP-NORM


(1) ABCC-PRT

Slot	Module	Order number	I Address	Q address	Diagnostic address	Comment
0	ABCC-PRT	ABCC-PRT			2043*	
X1	Interface				2042*	
P1	Port 1				2041*	
1	Output 1 word	ABCC-PRT		260...261		
2	Output 1 word	ABCC-PRT		262...263		
3	Output 1 word	ABCC-PRT		264...265		
4	Output 1 word	ABCC-PRT		266...267		
5	Input 1 word	ABCC-PRT	270...271			
6	Input 1 word	ABCC-PRT	272...273			

Ex: 4 * 1 word Output, 2 *1 word Input configuration



The sequence of IO module type in Master and blocks in Slave should be same. Recommend to define all Output modules first (Master to Slave) and then all input modules (Slave to Master) in sequence to minimize confusions in addressing. Make sure that continuous address used among Output modules and also among input modules.



Make sure that address selected is with in Process image OB1 P1

7.  You may need to create OB86 (Rack failure) in blocks during commissioning for testing purpose. If you do not program OB86, the CPU changes to STOP mode when a rack failure is detected. (When slave is not active or power on). Please refer Simatic Manager documentation for more information about OB86 and configure the same as per your application requirements



8. Compile PLC program, Save and download from PC to PLC



At this time, Bus failure LED will blink in S7-300 PLC because DP Slave is not available yet. If OB86 is not available in PLC, it may go to STOP mode. Once ProfiNet IO Slave configuration is completed in HMI and running properly, then, BF LED should stop blinking in Master



In ProfiNet IO module at Master side, Output4 word means, it is Int64/Uint64 type. This kind of data type is not supported in HMI at this time, so, please do not use. It is reserved for future use

In ProfiNet IO module at Master side, Output2 word means, it is Int32/Unit type. So, the valid block configuration for this kind of setup at HMI side is Blockn, Int32/Unit32 type, L=1, where n is block number

In ProfiNet IO module at Master side, Output1 word means, it is Int16/Unit16 type. So, the valid block configuration for this kind of setup at HMI side is Blockn, Int16/Unit16 type, L=1, where n is block number

Sample mapping between Master and Slave

Master to Slave


HMI side	PLC side	PLC address	Valid
Option-01 Block1, Int16 type, L=4, Read	Output 1 word Output 1 word Output 1 word Output 1 word	QB 260-261 or QW260 QB 262-263 or QW262 QB 264-265 or QW264 QB 266-267 or QW266	OK
Option-2 Block1, Int16 type, L=1, Read Block2, Int16 type, L=1, Read Block3, Int16 type, L=1, Read Block4, Int16 type, L=1, Read	Output 1 word Output 1 word Output 1 word Output 1 word	QB 260-261 or QW260 QB 262-263 or QW262 QB 264-265 or QW264 QB 266-267 or QW266	OK
Option-3 Block1, Int16 type, L=4, Read	Output 4 word	QB 260-267	Not valid

Slave to Master

HMI side	PLC side	PLC address	Valid
Option-1 Block1, Int16 type, L=4, Write	Input 1 word Input 1 word Input 1 word Input 1 word	IB 260-261 or QW260 IB 262-263 or QW262 IB 264-265 or QW264 IB 266-267 or QW266	OK
Option-2 Block1, Int16 type, L=1, Write Block2, Int16 type, L=1, Write Block3, Int16 type, L=1, Write Block4, Int16 type, L=1, Write	Input 1 word Input 1 word Input 1 word Input 1 word	IB 260-261 or QW260 IB 262-263 or QW262 IB 264-265 or QW264 IB 266-267 or QW266	OK
Option-3 Block1, Int16 type, L=4, Write	Input 4 word	IB 270-267	Not valid


7. HMI CONFIGURATION

1. In project explorer, double click at “Connections”
2. Click  to add a new connection.
3. Select Type= Other Network. Select Protocol = ProfiNet IO. Then click apply icon  to save this setup



	Name	Type	Parameter	Comment
▶	ProfiNet IO	Other Networks	ProfiNet IO	

4. Click “Config”  to open ProfiNet IO slave configuration
5. Enter IP address for the ProfiNet IO slave device (HMI). It should be unique in network. Please note that this IP address is for plug in module inserted in HMI to support ProfiNet IO slave functionality. The location is marked as COM3 in HMI. This IP address is not for standard Ethernet port in HMI's. It is also required to enter the same IP address in Simatic manager after adding slave as explained in section “PLC configuration”



Address	192 . 168 . 0 . 34
Mask	255 . 255 . 255 . 0
Gateway	192 . 168 . 0 . 10

- Select "Block". Add virtual IO modules as per requirement. Click "Apply" after completing the entries

The blocks defined here should be in same sequence as defined at PLC configuration, other wise, communication will not be succesful

ProfiNet IO

Communication | **Block**

Name	I/O Type	Data Type	Length	Comment
Block1	Read	Int16	4	Master to Slave
Block2	Write	Int16	2	Slave to Master

In above example, 4 nos. Int16 data will read from PLC to HMI and 2 nos. Int16 data will write from HMI to PLC

- Make sure that all the required IO modules are entered here completely as per the project requirements. Then, click "OK" to finish block configuration.

Tag

User Define | System | Conversion

1 /6

Connection: ProfiNet IO
 Name: ProfiNet_IO_Block1_0
 Read/Wri: Read & Write | Type: Analog
 Scan mode: Automatic | Scan rate: 100 ms
 Conversion: Disable
 Comment: Master to Slave

Register: ProfiNet IO.Block1.0
 Gain: 1
 Offset: 0

	Connection	Name	Type	Scan mode	Scan rate	Register	Comment
▶	ProfiNet IO	ProfiNet_IO_Block1_0	Analog	Automatic	100	ProfiNet IO.Block1.0	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_1	Analog	Automatic	100	ProfiNet IO.Block1.1	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_2	Analog	Automatic	100	ProfiNet IO.Block1.2	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_3	Analog	Automatic	100	ProfiNet IO.Block1.3	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block2_0	Analog	Automatic	100	ProfiNet IO.Block2.0	Slave to Master
	ProfiNet IO	ProfiNet_IO_Block2_1	Analog	Automatic	100	ProfiNet IO.Block2.1	Slave to Master

Ex: 4 words Read and 2 words Write

- In project explorer, double click "Tags" and check all the network tags. If required, it is possible to modify Tag names here. Once tag names are modified and linked with objects, do not attempt to modify configuration of blocks again at connections in Project explorer. Before modification of tag names in tag data base, make sure block settings are completely finished at Connections



After application download to HMI, it is a must to recycle power to HMI.

Switch OFF power supply to HMI and switch ON power supply to HMI. Then only networking application works properly. At power on, it might show message "Extension card fail" in HMI. Press "OK". If tags are linked with text boxes, it may show "Error" while reading data from Master to Slave. Once Master is started, communication will be established with slave and "Error" message disappears in objects and show real time data

8. CONVERTER

It is possible to do scaling in HMI application for Read/Write blocks

Task1: Read (Master to Slave)

PLC Value range=-32767 to 32767.

Convert this to 0 to 100 and display in HMI



Use Block1, Signed integer 16 type in HMI configuration

Task2: Write (Slave to Master)

Write 0 to 100 in HMI. Convert this to -32767 to 32767 and send to PLC

Use Block2, Signed integer 16 type in HMI configuration

Read, Block1_0		Write, Block2_0	
Value at PLC	Value Read in HMI	Value write in HMI	Value at PLC
-32767	0	0	-32767
0	50	50	0
32767	100	100	32767



Enter Scaling equation at "Conversion" tab

Tag

User Define | System | Conversion

1 /6

Connection: ProfiNet IO
 Name: ProfiNet_IO_Block1_0
 Read/Wri: Read & Write
 Type: Analog
 Scan mode: Automatic
 Scan rate: 100 ms
 Conversion: ProfiNet_IO_Conversion1
 Comment: Master to Slave

Register: ProfiNet IO.Block1.0
 Gain: 1
 Offset: 0

	Connection	Name	Type	Scan mode	Scan rate	Register	Comment
▶	ProfiNet IO	ProfiNet_IO_Block1_0	Analog	Automatic	100	ProfiNet IO.Block1.0	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_1	Analog	Automatic	100	ProfiNet IO.Block1.1	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_2	Analog	Automatic	100	ProfiNet IO.Block1.2	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block1_3	Analog	Automatic	100	ProfiNet IO.Block1.3	Master to Slave
	ProfiNet IO	ProfiNet_IO_Block2_0	Analog	Automatic	100	ProfiNet IO.Block2.0	Slave to Master
	ProfiNet IO	ProfiNet_IO_Block2_1	Analog	Automatic	100	ProfiNet IO.Block2.1	Slave to Master

Select required Conversion equation for the networking tags as shown above

9. EXAMPLES

9.1.1 4 words Read, 2 words write

Word data type addressing

IO module type at PLC	PLC address	HMI block address	HMI tag name	HMI IO type	Description
Output 1 word	QW260	Block1, length=4	Block1_0	Read	Master to Slave
Output 1 word	QW262		Block1_1	Read	Master to Slave
Output 1 word	QW264		Block1_2	Read	Master to Slave
Output 1 word	QW266		Block1_3	Read	Master to Slave
Input 1 word	IW270	Block2, Length=2	Block2_0	Write	Slave to Master
Input 1 word	IW272		Block 2_1	Write	Slave to Master

The screenshot displays the SIMATIC 300 Station configuration. The hardware rack is shown with the following modules:

- Slot 1: PS 307 2A
- Slot 2: CPU 315-2 PN/DP
- Slot X1: MPI/DP
- Slot X2: PN-IO
- Slot X2 P1: Port 1
- Slot 3: (Empty)
- Slot 4: AI4/AO2
- Slot 5: DI8/DO8xDC24V/0.5A
- Slot 6: (Empty)
- Slot 7: (Empty)
- Slot 8: (Empty)
- Slot 9: (Empty)
- Slot 10: (Empty)
- Slot 11: (Empty)

The DP-NORM module (ABCC-PRT) is configured in slot 0. Its configuration details are as follows:

Slot	Module	Order number	I Address	Q address	Diagnostic address	Comment
0	ABCC-PRT	ABCC-PRT			2043*	
X1	Interface				2042**	
P1	Port 1				2041*	
1	Output 1 word	ABCC-PRT		260...261		
2	Output 1 word	ABCC-PRT		262...263		
3	Output 1 word	ABCC-PRT		264...265		
4	Output 1 word	ABCC-PRT		266...267		
5	Input 1 word	ABCC-PRT	270...271			
6	Input 1 word	ABCC-PRT	272...273			

Fig: Master configuration

	Address	Symbol	Display format
33	QW 260		DEC
34	QW 262		DEC
35	QW 264		DEC
36	QW 266		DEC
37	MW 270		DEC
38	MW 272		DEC
39			

Fig: Variable table in S7-300 PLC

Name	I/O Type	Data Type	Length	Comment
Block1	Read	Int16	4	Master to Slave
Block2	Write	Int16	2	Slave to Master

Fig: HMI configuration



Note: Check length of block = 4 and data type = Int16 which is signed integer type to accept values between -32767 to + 32767

ProfNet IO

Communication | Block

Address: 192 . 168 . 0 . 34

Mask: 255 . 255 . 255 . 0

Gateway: 192 . 168 . 0 . 10

Fig: Typical slave configuration




Fig: Tags list in HMI software

9.1.2 8 bits Read, 8 bits write

Read, bytes = 1

Write, bytes = 1

Read + Write, bytes = 1+1=2 < maximum limit of 512 bytes, so it is possible.

IO module type	PLC address	HMI block address	HMI tag name	HMI IO type	Description
Output 1 byte	QB300	Block1	Block1	Read	Master to Slave
Input 1 byte	IB400	Block2	Block2	Write	Slave to Master




Fig: Master configuration




Fig: HMI configuration




Fig: Tags in HMI





Fig: HMI screen for testing digital I/O's

Var - VAT1

Table Edit Insert PLC Variable View Options Window Help

VAT1 -- 8Digital\SIMATIC 300 Station\CPU 315-2 PN/D

	Address	Symbol	Display format	Status value	Modify value
1	Q 300.0		BOOL		
2	Q 300.1		BOOL		
3	Q 300.2		BOOL		
4	Q 300.3		BOOL		
5	Q 300.4		BOOL		
6	Q 300.5		BOOL		
7	Q 300.6		BOOL		
8	Q 300.7		BOOL		

VAT2 -- 8Digital\SIMATIC 300 Station\CPU 315-2 PN/D

	Address	Symbol	Display format	Status value	Modify value
1	I 400.0		BOOL		
2	I 400.1		BOOL		
3	I 400.2		BOOL		
4	I 400.3		BOOL		
5	I 400.4		BOOL		
6	I 400.5		BOOL		
7	I 400.6		BOOL		
8	I 400.7		BOOL		

Fig: Variable table monitoring in PLC online




Fig: Indirect addressing to copy location IB4 to QB300

Network 2: Title:

It is to switch on Output in PLC digital output module QB4 directly from HMI via ProfiNet







Fig: Indirect addressing to copy location IB400 to QB4


10. FAQ

1. Can we order HMI first and then network extension card later? Can I fix network extension card myself?
Yes, it is possible.
2. All HMI support network extension card
Check HMI ordering code for Network extension card availability
3. After inserting network extension card, HMI is Master or Slave on specific network?
Slave
4. Is it possible to have more than 1 HMI in ProfiNet network
Yes, it is possible.
5. Is it possible to connect 1 HMI to 2 Masters on ProfiNet IO?
No, it is not possible.
6. Can I access Siemens PLC addressing areas directly in HMI software
No, it is not possible
7. What is the maximum data I can exchange between Master and Slave
Master to Slave: 256 bytes
Slave to Master: 256 bytes
Total: 512 bytes
8. Is GSDML Slave interface file is required to configure ProfiNet IO slave
Yes, Contact factory for GSDML file
9. What are the settings required in ProfiNet IO slave
You need to enter IP address for the ProfiNet IO slave in HMI configuration.
Then, you need to define blocks as per your data exchange requirements.
10. How many blocks I can add in ProfiNet IO slave at HMI configuration?
It depends on block length. By default, each block length = 1, Uint16 type. In above case, you can add 128 blocks of Read type and 128 blocks of Write type which occupies 256 bytes in each direction. This is equivalent to total 512 bytes.
11. I am getting message "Extension card fail" in HMI after power on.
Please switch OFF power supply to HMI and Power ON again after downloading application from PC to HMI.
12. How Can I exchange data between two slaves directly with out Master?
No, it is not possible. You must do this via Master only
13. How Can I install GSDML file into Simatic Manager?




14. I download application to PLC and HMI. But, in PLC, it is showing "BF" LED.

Please remove Ethernet cable from standard Ethernet port and connect to Ethernet port available at COM3 location. ProfiNet IO (Slave functionality) is supported at COM3 via Plug in module and not via standard Ethernet port



15. Simatic manager did not find ProfiNet IO slave device
Make sure ProfiNet IO network module is properly inserted in HMI. Download demo program (Analog) to HMI, Now, make sure Ethernet cable is connected at Ethernet port with location COM3, not at standard Ethernet port. Now press "RUN" at HMI from Control center. At this time, create a new project in Simatic manager and scan for Ethernet devices



Edit Ethernet Node [X]

Ethernet node

MAC address: Nodes accessible online

Set IP configuration

Use IP parameters

IP address: Gateway: Do not use router

Subnet mask: Use router
Address:

Obtain IP address from a DHCP server

Identified by


Client ID MAC address Device name

Client ID:

Assign device name

Device name:

Reset to factory settings



Note: If you download demo program to HMI, Plug in ProfiNet IO module, connect Ethernet cable at COM3, then, if you scan Ethernet devices, HMI should be detected as shown above. If not detected, then, there might be some issue in HMI configuration or Ethernet cable not properly connected at Plug in Module (Location: COM3) or some issues with Simatic manager itself

Edit Ethernet Node [X]

Ethernet node

MAC address: Nodes accessible online

Set IP configuration

Use IP parameters

IP address: Gateway

Subnet mask: Do not use router

Use router

Address:

Obtain IP address from a DHCP server

Identified by

Client ID MAC address Device name

Client ID:

Assign device name

Device name:

Reset to factory settings



Note: Please do not change Device name here. Other wise, communication will not work



If you Reset the slave, then, device name may become empty. In this case, you need to enter this manually